

HYVISION SHADOWLESS OT LIGHT

Sturdy, robust and
Efficient



Features:

- ✿ Shadowless Light with Electronic Focusing.
- ✿ 160,000 LUX in each dome
- ✿ Aluminium Outer body for heat Management
- ✿ Special hollow cavity design for Laminar flow compatibility
- ✿ 95 CRI Soft Light for long duration surgeries
- ✿ SS 304 Ceiling Fittings for Rust Protection
- ✿ Special Feather Touch Controllers for smooth controls in 6-10 steps

SPECIAL FEATURES:

Our Shadow less OT Light is USFDA Certified and is made out of medical grade stainless steel and aluminium that prevents rusting and gives efficient results for years to come.



AN ISO 9001 : 2015 Co., with ISO 13485 & CE Mark.

Manufacture of Medical Equipments & Centralized Medical Gas Pipeline Systems

Customized Medical Trolleys with Hospital Furniture

139, Bhakrahat Road, Haspukur, Thakurpukur, Joka, Kolkata – 700 104.

Mob : 98301 31604, E-Mail : jamexmeditech@gmail.com

Web : www.jamexmeditech.co.in



Authorized Distributor

Double Dome LED OT Light



Specification

Intensity	2,00,000 LUX + 2,00,000 LUX
Shadow less Features	Yes
Numbers of LEDs	144 + 144 (Warm + Cool White)
Intensity Control	10-100 Digital Capacitive Touch (Fully Remote Control)
Fitting Options Available	Celling Wall Mounted – 3400 Degrees/ 360 Degrees
Spot Diameter	100 – 150 mm
Depth of Light penetration	150 mm
Colour Temperature	3800 – 4800K
Colour Rendering Index	93 Ra
Focusing	Adjustable
LED Average Life	>50,000 Hrs.
Diameter of light	700 mm + 700 mm
Power Supply	220V/50Hz AC
Power Consumption	100 + 100 Watt
Optional Special Features	Mobile App Connectivity, External Wall Panel, Battery Backup

Features

Fully Aerodynamic German design for laminar flow, Clear Vision Technology for better viewing during long hours of surgery, Shadowless Light, Memory Function, High Quality Sterilizable Handle suitable for Autoclave. Unbreakable Fire-Resistant Polycarbonate Body, Fast Disinfection Process, Protects UV and IR rays and Improves light penetration for deep cavity surgeries.

Single Dome LED OT Light

Specification

Intensity	2,00,000 LUX
Shadow less Features	Yes
Numbers of LEDs	144 (Warm + Cool White)
Intensity Control	10-100 Digital Capacitive Touch (Fully Remote Control)
Fitting Options Available	Celling Mounted
Spot Diameter	100 – 150 mm
Depth of Light penetration	150 mm
Colour Temperature	3800 – 4800K



Mobile Type



Features

Fully Aerodynamic German design for laminar flow, Clear Vision Technology for better viewing during long hours of surgery, Shadowless Light, Memory Function, High Quality Sterilizable Handle suitable for Autoclave. Unbreakable Fire-Resistant Polycarbonate Body, Fast Disinfection Process, Protects UV and IR rays and Improves light penetration for deep cavity surgeries.